## IN THE CLAIMS:

Please amend claims 1, 5, and 6 as follows:

. 1. (Currently Amended) A singing voice synthesizing apparatus, comprising:

a singing voice information input device that inputs singing voice information for synthesizing a singing voice;

a phoneme database that stores voice synthesis unit data;

a selector that selects the voice synthesis unit data stored in the phoneme database in accordance with the singing voice information;

a timbre transformation parameter input device that inputs a timbre transformation parameter for transforming timbre, the timbre transformation parameter including a coefficient  $\alpha$  indicating whether a singing voice is made to be feminine or masculine;

a mapping function generator that generates, in accordance with the coefficient included in the timbre transformation parameter, a mapping function defined by a following equation (1)  $fout = (fs/2) \times (2 \times fin / fs)^{\alpha} \quad (1),$ 

where fout is an output frequency, fs is a sampling frequency, fin is an input frequency and  $\alpha$  is the coefficient indicating whether the singing voice is made to be feminine or masculine; and

a singing voice synthesizer that adjusts generates a spectrum envelope generated based on the selected voice synthesis unit data, transforms the generated spectrum envelope in accordance with the mapping function generated by using a local peak frequency of the spectrum envelope as the input frequency, and generates a synthetic singing voice of which character is changed by transforming the voice synthesis unit data in accordance with the timbre transformation parameter using the transformed spectrum envelope.

2. (Previously Presented) A singing voice synthesizing apparatus according to claim 1, further including a characteristic parameter output device that derives a characteristic parameter from the voice synthesis unit data selected by the selector and outputs the derived characteristic parameter, and wherein the singing voice synthesizer corrects the characteristic parameter in accordance with the timbre transformation parameter.

## 3. (Canceled)

- 4. (Previously Presented) A singing voice synthesizing apparatus according to claim 1, wherein the timbre transformation parameter input device includes a timbre transformation parameter adjuster that changes the timbre transformation parameter in a time axis.
- 5. (Currently Amended) A singing voice synthesizing method, comprising: inputting singing voice information for synthesizing <u>a</u> singing voice; storing voice synthesis unit data into a phoneme database in advance and selecting the

voice synthesis unit data stored in the phoneme database in accordance with the singing voice information;

inputting a timbre transformation parameter for transforming a timbre, the timbre transformation parameter including a coefficient α indicating whether a singing voice is made to be feminine or masculine;

generating, in accordance with the coefficient included in the timbre transformation parameter, a mapping function defined by a following equation (1)

fout =  $(fs/2)^{\alpha} x (2 x fin/fs)^{\alpha} (1)$ 

where fout is an output frequency, fs is a sampling frequency, fin is an input frequency, and α is the coefficient indicating whether the singing voice is made to be feminine or masculine; adjusting generating a spectrum envelope generated based on the selected voice synthesis unit data in accordance with the timbre transformation parameter;

transforming the generated spectrum envelope in accordance with the mapping function generated by using a local peak frequency of the spectrum envelope as the input frequency; and generating a synthetic singing voice of which character is changed by transforming the voice synthesis unit data in accordance with the timbre transformation parameter using the transformed spectrum envelope.

6. (Currently Amended) A computer-readable storage medium having encoded thereon a singing voice synthesizing program including instructions which when executed by a computer causes:

inputting singing voice information for synthesizing a singing voice;

storing voice synthesis unit data into a phoneme database in advance and selecting the voice synthesis unit data stored in the phoneme database in accordance with the singing voice information;

inputting a timbre transformation parameter for transforming timbre, the timbre transformation parameter including a coefficient α indicating whether a singing voice is made to be feminine or masculine;

generating, in accordance with the coefficient included in the timbre transformation parameter, a mapping function defined by a following equation (1)

## fout = (fs/2) x (2 x fin/fs) $\alpha$ (1)

where fout is an output frequency, fs is a sampling frequency, fin is an input frequency, and  $\alpha$  is the coefficient indicating whether the singing voice is made to be feminine or masculine; adjusting generating a spectrum envelope generated based on the selected voice synthesis

unit data in accordance with the timbre transformation parameter;

transforming the generated spectrum envelope in accordance with the mapping function generated by using a local peak frequency of the spectrum envelope as the input frequency; and generating a synthetic singing voice of which character is changed by transforming the voice synthesis unit data in accordance with the timbre transformation parameter using the

///

transformed spectrum envelope.

1//

///

///

///

111

///

///

111

///

///